# TAD1351-1353VE

NEW!

13 litre, in-line 6 cylinder - 285, 315 & 345 kW

UNECE Reg 96 Power band H (equal to EU Stage IIIA)

TAD1351-1353VE is a powerful, reliable and economical off-road Diesel Engine range built on the Volvo Group in-line six concept.

### Low cost of ownership

World class fuel efficiency combined with high uptime as well as low cost of ownership.

# Compact & simple installation

As optional equipment all material needed in order to install the engine can be ordered from Volvo Penta. Installation guidelines as well as drawings and CAD models are easy to access. The result is an engine that is easy to install.

### **Durability & low noise**

Long experince with base engine development reduces risk of downtime. Well-balanced to produce smooth operation with low noise.

### **Power & torque**

Maximum power and torque available at low rpm. As a result noice as well as fuel consumption is very low. Useful engine speed for the TAD1351-1353VE is due to power and torque layout very flexible.

### Low exhaust emission

Efficient injection as well as robust engine design in combination with internal EGR contributes to excellent combustion and low fuel consumption.

### Easy service & maintenance

Easily accessible service and maintenance points contribute to the ease of service of the engine. As optional equipment possible to remote mount filters and service points.



- Proven and straight-forward design built on Volvo Group technology
- · Low cost of ownership and operation
- · High power and torque already at low engine speed
- · Compact, simple installation and easy to service
- · Similar engine footprint for all emission standards
- High sulfur-in-fuel tolerance
- Wide range of optional equipment

### **Technical description**

### Engine and block

- Cast iron cylinder block
- · Wet, replaceable cylinder liners
- Replaceable valve guides and valve seats
- Overhead camshaft and four valves per cylinder

### Lubrication system

- Full flow disposable spin-on oil filter, for extra high filtration
- Gear type lubricating oil pump, gear driven by the transmission
- Oil level sensor at startup

### Fuel system

- · Electronic high pressure unit injectors
- Fuel prefilter with water separator and waterin-fuel indicator / alarm
- · Gear driven low-pressure fuel pump
- Fine fuel filter with manual feed pump and fuel pressure switch

### Cooling system

- Available as power pack or base engine.
- Belt driven coolant pump with high degree of efficiency

### Turbo charger

• Electronically controlled Waste-gate

### Electrical system

- Engine Management System (EMS) 2.3, an electronically controlled processing system which optimizes engine performance. It also includes advanced features for diagnostics and fault tracing.
- The instruments and controls connect to the engine via the CAN SAE J1939 interface.
   Options available for engine control equipment.

### Exhaust reduction system

· With internal EGR



## TAD1351-1353VE


### **Technical data**


Engine designation	TAD1351-1353VE
Configuration and no. of cylinders	in-line 6
Displacement, I (in <sup>3</sup> )	12.78 (780)
Method of operation	4-stroke
Direction of rotation (viewed towards flywheel)	anti-clockwise
Bore, mm (in.)	131 (5.16)
Stroke, mm (in.)	158 (6.22)
Compression ratio	17.8:1
Dry weight, engine only, kg (lb)	1276 (2813)

Engine	kW	Нр	rpm	Max Nm
TAD1351VE	285	388	1900	1965
TAD1352VE	315	428	1900	2175
TAD1353VE	345	469	1900	2380


### **Dimensions**

Not for installation. Dimensions in mm.





# Power, kW 350 315 280 245 210 175 140 105 — TAD1351VE 70 — TAD1352VE 35 — TAD1353VE



800

1000

1200

1400


Engine speed, rpm

1600

1800

2000

2200



### Power standards

The engine performance corresponds to ISO 3046, BS 5514 and DIN 6271. The technical data applies to an engine without cooling fan and operating on a fuel with calorific value of 42.7 MJ/kg (18360 BTU/lb) and a density of 0.84 kg/litre (7.01 lb/US gal, 8.42 lb/lmp gal), also where this involves a deviation from the standards.

### **Additional information**

For additional information, please contact your Volvo Penta representative or visit www.volvopenta.com.



AB Volvo Penta SE-405 08 Göteborg, Sweden www.volvopenta.com